



POSSIFY

“Simple, Robust & Reliable”

- Super thin Display with True-Flat Projected Capacitive Multi Touch
- Multiple I/O Ports (up to 11 USB, 3 COM & 2 LAN ports)
- Anodized Aluminum and Robust Frame Design



Model : POSSIFY VOLL156 Windows POS Terminal

Processor	Intel® Processor N97 (Alder Lake), 6M Cache, Max. 3.6 GHz Optional: Intel® Core™ i3-N300, 6M Cache, Max. 3.80 GHz
Operation System	Windows 10/11 and Linux
System Memory	DDR4 SO-DIMM 8GB (3200MTs, up to 16GB)
Storage	M.2 SSD 256GB (PCIe 3.0 x 2 NVMe / SATA 3.0)
LCD Panel	15.6-inch Full HD LCD, 1920 x 1080
Touch Panel	True-Flat Projected Capacitive Multi Touch
Expansion Slot	M.2 M-Key 2230, PCIe x1 + USB2.0 MINI-PCIE, PCIe x1 + USB2.0 + SIM
Interface	2xUSB 3.2 Type A, USB 3.2 Type C (DP ALT, DC OUT(5V@3A, 12V@3A), 8xUSB 2.0 Type A, RJ45 10/100/1000Mbps Giga Ethernet, 2xCOM (RJ45), 5V/12V by BIOS, COM (RS232), RI / 5V/12V by jumper, HDMI Port, Line-out / MIC-in, RJ11 port supports 2 cash drawer, 12V/24V by jumper, DC Jack 2.5mm
Operation Condition	0°C to +40°C / 20 to 80% without condensation
Storage Condition	-20°C to +55°C / 20 to 85% without condensation
Speaker	2W High Quality Speaker
Power Adapter	12V/5A 60W Adapter (System)
Dust and Water	IP65 on Front Panel
Dimension	365 (W) x 182 (D) x 338 (H) (mm)
Weight	4.0 kg
Certification	CE/FCC/LVD
TPM	FTPM
Optional	2nd Display: 10.1" (1280x800) / 15.6" (1920x1080), LCD Display, PCAP Touchscreen, Wi-Fi: Wi-Fi IEEE 802.11 a/b/g/n/ac



* Specifications are subject to change without prior notice.

“Simple, Robust and Reliable”

www.possify.com.tr

info@possify.com.tr